Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com



Document created on 05-29-19

## 20QT (Gen 2) Elite

Pelican Products, Inc. has protected defense, emergency and scientific expedition equipment through some ofthe harshest conditions on Earth since 1976. This same DNA is now available to you in Pelican<sup>™</sup> Elite Coolers. We hold ourselves to higher criteria than other cooler makers. When it comes to durability, performance and ergonomic design, just "good enough" doesn't cut it. As a result, Pelican<sup>™</sup> Elite Coolers perform to higher standards — better than any cold locker, tougher than any icebox. Pelican<sup>™</sup> Elite Coolers are true next-generation innovations, created to last a lifetime.

From the latches to the freezer-grade seal to the toughest handles in the business, every part is engineered to our extreme durability and performance standards. Which is why we feel confident in providing you with a Lifetime Guarantee. Not three years. Not five years. A lifetime. Something the other makers don't (or can't) do.

Whether you're on the hunt of a lifetime, far out at sea with a cooler full of catch, crossing deserts on safari or simply tailgating during a big game – the Pelican™ Elite Cooler is the one for you.



- Press & Pull Latches
- Molded-In Tie Downs
- Non-Skid & Non-Marking Raised Feet
- Guaranteed for life
- Integrated Cup Holders

## DIMENSIONS

Interior (L x W x D)	12.00 x 6.70" x 14.10 (30.5 x 17 x 35.8 cm)
Exterior (L x W x D)	18.80 x 12.60" x 17.70 (47.8 x 32 x 45 cm)
Volume	21.50QT (20.35 L)
Int Volume	0.66 ft³ (0.019 m³)
Insulation Thickness	0.78" (2 cm)

## MATERIALS

Body	Poly	propylene				
Latch	ABS					
Handle	Poly	propylene				
Hardware	Stair	less Steel				
Insulation	Poly	urethane Foam				
COLOR	S					
White - Gray	Green - Tan	Tan - Orange	Seafoam - Gray	Dark Gray - Green	Realtree Edge	Realtree Fish
WEIGH <sup>-</sup>	Г					

Weight

12.52 lbs (5.7 kg)

## ACCESSORIES

